

E.F.I. Outboards

Model	F60	F50	F40	F30	F20	F6
Max. Power	60HP/44.1Kw	50HP/36.8Kw	40HP/29.4Kw	30HP/22Kw	20HP/14.7Kw	6HP/4.4Kw
Engine type	4-cyl. SOHC	4-cyl. SOHC	3-cyl. SOHC	3-cyl. SOHC	2-cyl. SOHC	1-cyl. OHV
Displacement	996cc	996cc	747cc	747cc	362cc	148cc
Bore x Stroke	65.0x75.0mm 2.56x2.95in.	65.0x75.0mm 2.56x2.95in.	65.0x75.0mm 2.56x2.95in.	65.0x75.0mm 2.56x2.95in.	63.0x58.1mm 2.48x2.29in.	64.0x46.0mm 2.52x1.8in.
Max. RPM Range	5000~6000	5000~6000	5000~6000	5000~6000	5000~6000	4500~5500
Idling RPM Range	750~850	750~850	900~1000	900~1000	1000~1100	1450~1550
Sump Oil Capacity	2.5L	2.5L	1.7L	1.7L	1.6L	0.5L
Ignition Timing	Micro Computer	Micro Computer	Micro Computer	Micro Computer	Micro Computer	Micro Computer
Starting System	Electric	Electric	Electric+Manual or Electric	Electric+Manual or Electric	Electric+Manual or Manual	Manual
Steering System	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller or Remote	Tiller
Trim and Tilt	Gas assist or Electric	Gas assist or Electric	Gas assist or Electric	Gas assist or Electric	Manual	Manual
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Gear Ratio	1.85	1.85	2.0	2.0	1.85	2.15
Gear Oil Capacity	430cc	430cc	430cc	430cc	250cc	195cc
Transom Height	20in.	20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.	15in. or 20in.
Dry Weight*	113kg	113kg	94kg	94kg	51.7kg	27kg
Alternator Output*	12V, 25A	12V, 25A	12V, 25A	12V, 25A	12V, 6A	12V, 6A
Fuel Tank	24L	24L	24L	24L	24L	Build-in 1.3L
Propeller* (pitch)	12", 13"	12", 13"	12", 13"	12", 13"	8", 10", 11", 12"	9"

*Vary on models